

DERRICK PIN DRIVERS

BHDE DERRICK PIN DRIVERS

BHDE Derrick Pin Drivers are designed for safety. When removing derrick pin, the "Flex Handle" and distance from the point of impact make the pin driver a must safety item on every rig.



DERRICK PIN DRIVERS

DESCRIPTION	WT. LBS.	PART NO.
1" Derrick Pin Driver	12	K078DPD
1 1/4" Derrick Pin Driver	22	K114DPD
1 5/8" Derrick Pin Driver	25	K158DPD
2" Derrick Pin Driver	30	K200DPD

BUG BLOWERS



48" Bug Blower



24" Bug Blower

	PART NO. 48B	PART NO. 24B
SPECIFICATION	DESCRIPTION	DESCRIPTION
Unit Dimensions	Base: 72" H x 50" W x 28" D	40" H x 48" W x 18.5" D
Base Construction	4" x 1/4" "C" Channel	4" x 1/4" "C" --Channel
Motor	230/460V, 1765 RPM, 60 Hz-EP- 3/5 HP	230/460V, 1765 RPM, 60 Hz-EP- 2 HP
Electric Box/Cable	AB609-BEW - CAROL 4/c 10AWG	AB609-BEW - CAROL 4/c 10AWG
Fan Housing	50" Diameter, 1/8" Angle & 16 ga Sheet	28" Diameter, 1/8" Angle & 16 ga Sheet
Fan Blades	40" Cast Aluminum	24" Cast Aluminum
Fan Guards	49" Diameter SS Grate	28" Diameter SS Grate
Weight Lbs.	480	280



A DIVISION OF BOB HERBERT & ASSOCIATES, INC.
www.bhde.com