

STANDPIPE PRESSURE GAUGES

STANDPIPE PRESSURE GAUGES

To Order Specify

- Capacity
- English, Metric, or dual scale divisions
- Hammer union and sub size (hammer union type only)
- Flange size and pressure capacity of flange (flange type only)
- Ring groove size (flange type only)
- Standard or H2S service

BHDE offers Standpipe Pressure Gauges with a variety of connections including 2" male npt, hammer union type, and flanged type. These gauges integrate a 6" inverted gauge with a heavy duty housing and include a check valve and damper assembly incorporated into housing. These gauges are ideal for use on pumps, pump trucks, standpipe, choke manifolds, and pipeline pressure applications.

Features

- Replaceable diaphragm cup, check valve, and damper assembly
- Standard capacities up to 15,000 psi
- Dial available in English, Metric, or dual scale divisions
- Hammer union type available in 1502 or 2202 for standard or H2S service
- Flange type available in a variety of flange sizes (contact BHDE for specifics)
- Flange type and hammer union type available with DNV or ABS certification
- Large 6" dial face is visible for up to 75 feet away

Benefits

- Fluid-filled case keeps internal components lubricated and reduces vibration
- Damper assembly reduces vibration and pointer oscillations
- Durable fluid filled design with built-in damper increases component life and reduces maintenance costs



A DIVISION OF BOB HERBERT & ASSOCIATES, INC.
www.bhde.com