

BHDE THRED-LOK KIT



**Kit Includes
Base Resin,
Catalyst,
Applicator**

BHDE THRED-LOK KIT

The BHDE Thred-Lok Kit is a complete two-component epoxy system that includes base resin, catalyst and applicator. It is designed for use on all threaded joints and is especially applicable on OCTG casing and other pipe where the effective prevention of joint-loosening and casing backing-off is required.

Application Information

The catalyst is emptied into the can containing the base epoxy resin and the two are thoroughly mixed. The applicator is used to completely cover the male threads with the mixture, and the joint is then made up. A workable consistency averages 75 minutes. Complete cure occurs in 24 hours, after which connections may be broken by heating to 550°F (288°C).

Features

- Complete Kit with instructions
- Color: Grey
- * Pot Life: 75 minutes (avg)

Benefits

- Easy application
- Adheres to any clean surface
- Prevents back-off
- Non-corrosive
- Non-conductive
- Resistant to acids, solvents and water
- Economical

Cautions

- Do not use on oxygen lines
- Dangerous to skin and eyes
- Use rubber or plastic gloves and goggles
- Mix in well-ventilated area
- Can will become hot to the touch when catalyst is mixed in. Always wear gloves to shield hands from heat.

BHDE THRED-LOK KIT			
PART NO.	KIT SIZE	KITS / CASE	SHIPPING WT.
19950BLK	8 Oz.	12	6 Lb.
19951BLK	16 Oz.	6	6 Lb.

APPROX. CAPACITY PER 8 Oz. KIT	
CASING O.D. IN.	NUMBER OF JOINTS
4 ¹ / ₂	10
5 ¹ / ₂	5
6 ¹ / ₂ - 7	4
7 ⁵ / ₈ - 8 ⁵ / ₈ - 9 ⁵ / ₈	3
10 ³ / ₄ - 11 ⁵ / ₈ - 13 ⁵ / ₈	2
16 - 20	1



A DIVISION OF BOB HERBERT & ASSOCIATES, INC.
www.bhde.com